

対象商品 高強度羽子板ボルト

建物高さ		5M																	
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165			φ 216		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50																		
	60									1200									
	70																		
	80																		
	90																		
	100																		
	110	1200			1200	1200													
	120																		
	130																		
	140																		
	150																		
	160																		
	170																		
	180																		

建物高さ		9M																	
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165			φ 216		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50																		
	60																		
	70																		
	80																		
	90																		
	100																		
	110	1200			1200	1200													
	120																		
	130																		
	140																		
	150																		
	160																		
	170																		
	180																		

建物高さ		13M																	
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165			φ 216		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50																		
	60																		
	70																		
	80																		
	90																		
	100																		
	110	1200	1200	1200	1200														
	120																		
	130																		
	140																		
	150																		
	160																		
	170																		
	180																		

建物高さ		31M																	
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165			φ 216		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50																		
	60																		
	70																		
	80																		
	90																		
	100																		
	110	1200	1200		1200														
	120																		
	130																		
	140																		
	150																		
	160																		
	170																		
	180																		

下記の諸元を元に計算した結果

諸元
 基準風速V₀ 34m/s
 ピーク風力係数 1.2

備考
 地表面粗度区分Ⅱ:高さ13m以下の場合を除く