

対象商品 高強度羽子板ボルト

建物高さ		5M														
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50															
	60									1200			900			
	70															
	80															600
	90						1200									
	100									900						
	110	1200		1200	1200			1200			1200			1200		
	120												600			
	130															
	140															
	150															
	160						900			600						
	170															
	180													900		

建物高さ		9M														
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50															
	60									1200						
	70															
	80						1200							1200		600
	90									900			600			
	100															
	110	1200		1200	1200			1200			1200					
	120															
	130															
	140						900									
	150									600						
	160													900		
	170															
	180						600				900					

建物高さ		13M														
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50															
	60															
	70															
	80								1200	900			600	1200		900
	90										1200	900				
	100						1200									
	110	1200	1200	1200	1200			1200							600	
	120						900									
	130									600				900		
	140								900							
	150											600				
	160										900					
	170							600								
	180						900		600							

建物高さ		31M														
バンドサイズ		φ 60			φ 76、φ 89			φ 114			φ 140			φ 165		
地域		III	II	I	III	II	I	III	II	I	III	II	I	III	II	I
長さ	50															
	60						1200		1200		1200	900				
	70												600	900	600	
	80						1200									
	90			1200				1200	900							
	100						900			600	900	600				
	110	1200	1200		1200											
	120															
	130													600		
	140															
	150						900	600		600						
	160								900			600				
	170			900												
	180						600									

下記の諸元を元に計算した結果

諸元
 基準風速Vo 34m/s
 ピーク風力係数 1.2

備考
 地表面粗度区分Ⅱ:高さ13m以下の場合を除く